



855.014-6 ES

**Male branch tee, a/fivel type, parallel male thread with O-ring (FPM)**

Art. No.	Type No.	T For tube O.D. mm	P Thread	B mm	D mm	L1 mm	L2 mm	A/F1 mm	A/F2 mm	Standard thread
135172	855.005-4 ES	4	M5	5.0	10.0	20.3	24.0	10	11	DIN 13-1
135173	855.018-4 ES	4	G 1/8	5.8	10.0	20.3	24.9	10	14	DIN EN ISO 228-1
135174	855.018-6 ES	6	G 1/8	5.8	12.4	22.1	26.0	12	14	DIN EN ISO 228-1
135175	855.018-8 ES	8	G 1/8	5.8	14.0	23.2	27.0	14	14	DIN EN ISO 228-1
135176	855.014-4 ES	4	G 1/4	7.5	10.0	20.3	26.8	10	17	DIN EN ISO 228-1
135177	855.014-6 ES	6	G 1/4	7.5	12.4	22.1	28.0	12	17	DIN EN ISO 228-1
135178	855.014-8 ES	8	G 1/4	7.5	14.0	23.2	29.0	14	17	DIN EN ISO 228-1
135179	855.014-10 ES	10	G 1/4	7.5	16.5	24.3	30.3	16	17	DIN EN ISO 228-1
135180	855.014-12 ES	12	G 1/4	7.5	19.0	26.7	32.8	19	19	DIN EN ISO 228-1
135181	855.038-8 ES	8	G 3/8	7.5	14.0	23.2	29.5	14	21	DIN EN ISO 228-1
135182	855.038-10 ES	10	G 3/8	7.5	16.5	24.3	30.7	16	21	DIN EN ISO 228-1
135183	855.038-12 ES	12	G 3/8	7.5	19.0	26.7	32.6	19	21	DIN EN ISO 228-1
135184	855.038-14 ES	14	G 3/8	7.5	21.8	28.7	35.4	22	22	DIN EN ISO 228-1
135185	855.012-10 ES	10	G 1/2	10.0	16.5	24.3	33.8	16	27	DIN EN ISO 228-1
135186	855.012-12 ES	12	G 1/2	10.0	19.0	26.7	35.8	19	27	DIN EN ISO 228-1
135187	855.012-14 ES	14	G 1/2	10.0	21.8	28.7	38.4	22	27	DIN EN ISO 228-1
135188	855.012-16 ES	16	G 1/2	10.0	23.3	30.0	39.6	24	27	DIN EN ISO 228-1